

SIGNATURE ALBATROSS

General Carton Guidelines

For cartons smaller or larger than indicated, please call AIM to evaluate the machine's capabilities at 414.764.3223.

DESCRIPTION			Model 220	Model 300
STRAIGHT LINE CARTONS	B	(mm)	290 ~ 2200	290 ~ 3000
	L	(mm)	140 ~ 1600	140 ~ 1600
	C	(mm)	130 ~ 1080	130 ~ 1470
LOCK BOTTOM CARTONS	B	(mm)	310 ~ 2100	310 ~ 2800
	L	(mm)	190 ~ 1600	190 ~ 1600
	C	(mm)	140 ~ 1035	140 ~ 1370
4-CORNER COLLAPSIBLE BOXES	B	(mm)	290 ~ 2000	290 ~ 2800
	L	(mm)	250 ~ 1600	250 ~ 1600
	H	(mm)	50 ~ 250	50 ~ 250
6-CORNER COLLAPSIBLE BOXES	B	(mm)	500 ~ 1600	500 ~ 2400
	L	(mm)	250 ~ 1000	250 ~ 1000
	H	(mm)	50 ~ 250	50 ~ 250
HEAVY SOLID BOARD			32-60 point (800 – 2000 gm ²)	32-60 point (800 – 2000 gm ²)
CORRUGATED BOARD			N, F, E, B, C, AB, AC, BC, EB, EF	N, F, E, B, C, AB, AC, BC, EB, EF
SPEED			30 ~ 250 m/min	30 ~ 250 m/min
INCHING SPEED			20 m/min	20 m/min
THICKNESS OF CARTONS			35mm max	35mm max
MACHINE LENGTH			24.900 M	24.900 M
MACHINE WEIGHT			19,000 kg	24,000 kg
TOTAL CONNECTED LOAD			95 KVA	95 KVA