



SIG-PACK





FEATURES:


- Run speed up to 200,000 blanks per hour
- Convertible stock: solid board: 200-650 g/m2; straightline box type
- \bullet Fills outer box (shipping case) sizes max. 550(w) x 700(l) x 400(h) mm and min. 160(w) x 300(l) x 100(h) mm
- \bullet Fills inner box (folded carton) sizes max. 400(w) x 550(l) mm and min. 50(w) x 100(l) mm
- Compatible with most folder gluer brands
- Micro adjustments can be made during operation

SIGNATURE SIG-PACK


With the never-ending push for improved return on investment, the Signature line of converting technology provides a reliable and rapid payback.

Compatible Inline Supplementary Unit

The Signature Sig-Pack carton packer is compatible with most folder gluer brands and is available for sale as an individual unit or as a supplemental option for a new Signature brand folder gluer. Designed for continuous operation at any speed, the Sig-Pack is known for accurate box counts, simple maintenance, operator friendliness and energy efficiency making it a productive and profitable solution for any converting operation.




Inline Configuration




Measurements in millimeters (mm). Base model air requirements: 90 PSI. Base model power requirements: 380V / 3 phase / 60 amps. Based on configuration of specific machine, power and air requirements may change and additional transformers may be required. Contact your AIM representative to confirm.

L-Shape Configuration



CARTON SPECIFICATIONS


2 OR 4 CREASE LINE



A: 100-500 mm

B: 50-400 mm

CONTAINERS (with or without closing flaps)



C: 300-700 mm

D: 160-600 mm

E: 100-420 mm



